

## Loop Driver Card

The Loop Driver Card is designed for use with the MxPro 5 range of analogue addressable panels. It provides control and connection to detector loops.

The Loop Driver Card Mxp-502 can be used with Apollo, Hochiki or Argus Vega protocols.

The Loop Driver Card Mxp-567 can be used with the Nittan protocol.

### Features

- Use with MxPro 5 analogue addressable panels
- Mxp-502 is compatible with Apollo, Hochiki and Argus Vega protocols
- Mxp-567 is compatible with Nittan protocol

### Specification

Power Supply	24V DC
Protocols	Apollo S90I XP95, Discovery, Explorer / Hochiki ESP / Argus Vega / Nittan Evolution
Devices per Loop (maximum)	Apollo 126 detector/call points per loop Hochiki 127 detector/call points per loop Argus 240 detector/call points per loop Nittan 249 detector/call points per loop
Loop Current	500 mA max

### Order Codes and Options

Mxp-502:	Loop Driver Card - Apollo, Hochiki and Argus Vega
Mxp-567:	Loop Driver Card - Nittan

[Check if this document is up to date](#) | [Give us feedback](#)

Advanced, The Bridges, Balliol Business Park, Newcastle upon Tyne, NE12 8EW, UK **T:** +44 (0)345 894 7000, **E:** [enquiries@advancedco.com](mailto:enquiries@advancedco.com),  
**W:** [www.advancedco.com](http://www.advancedco.com)

As our policy is one of constant product improvement the right is therefore reserved to modify product specifications without prior notice.